

Ref: AD1B/L-(R290)



Your professional partner

Ventilated freezer 700 liters, 1 door GN 2/1

Brand : DIAMOND



·mm (BxDxH) :750x820xh2025

·T° : -15° -25°

·kW :0,5

·Volt : 230/1N 50Hz

·kg : 165

·M³ : 1,5

- Included: 3 grids GN 2/1 (530x650 mm).
 - Inner door with warm resistance.
 - Depression valve, standard delivered .
 - 4 adjustable stainless steel feet.
 - Manufactured in stainless steel, inside and outside in AISI 304 (back in galvanized steel), monocoque frame.
 - Stainless steel rack and slides (anti-tilting), allowing to place the grids as one pleases, stamped interior bottom, rounded angles and corners (without roughness).
 - Doors with ergonomic handle (no salient) and reversible, "snap-fit" closure by magnetic joint (easy replacement without tools), hinges with stop at 100° and closure of the doors with automatic recall.
 - Micro-switch device, allowing the ventilator's stop, while opening the door.
 - Standard delivered with key lock.
 - Upper panel for the accessibility of the compressor, on hinges, easy inspection.
 - Tropicalized compressor group (ambient T° +43°C), ventilated condenser.
 - Over-sized evaporator, ventilated or static, treated against the salt and the food acids "coating", completely hidden (non apparent).
 - Refrigerant R290.
 - "Digital" electronic microprocessor (under closed box, 100% waterproof) with HACCP functions, front screen control with blue LED.
 - Intern lighting type LED, with switch.
 - Automatic defrosting of the evaporator (by warm gas), number of defrosting programmed by factory (modifiable at will).
 - Condenser's automatic evaporation (by warm gas).
 - Polyurethane insulation without CFC (75 mm = super insulated).
 - The equipment is manufactured following the (CE) standards in force.
- PLUS :
- Refrigerated group "tampon", tropicalized (+43°C).
 - Polyurethane insulation without CFC, thickness 75 mm "super insulated".
 - Exceptional services thanks to a homogenous distribution of the refrigerated air ("lateral flux") allowing an uniform temperature, guaranteeing the right preservation of the products (no drying the food in the refrigerator).
 - For delicate products (ex. pastries, etc.), possibility to activate the function (in the microprocessor), 2 levels of hygrometric regulation.
 - Regulation microprocessor (under closed box, 100% waterproof)