



10/2016

# **Mod: N65/R212G/EL**

**Production code: 10121701-Q-0-0 (U3)**



**Diamond**  
catering equipment

Model	N65/R212G/EL	N65/R316G/EL
		
Production code	10121701-P-0-0	10121702-P-0-0
Description	Refrigerated base, with special feet H95/155	Refrigerated base, with special feet H95/155
Light	no	no
Key lock	no	no
Range (°C)	-2° +8°	-2° +8°
Operating Mode	Ventilated	Ventilated
<b>External Dimensions</b>		
Width (mm)	1200	1600
Depth/with open drawers (mm)	600 / 1195	600 / 1195
Worktop height (mm)	615 / 675	615 / 675
<b>Internal Dimensions</b>		
Width (mm)	780	1215
Depth (mm)	495	495
Height (mm)	410	410
Gross capacity (L)	158	247
<b>Defrost</b>		
Type of defrost	Automatic	Automatic
No. of defrost in 24h	4	4
Evaporation of defrost water	Automatic	Automatic
<b>Compressor</b>		
Brand	Cubigel	Cubigel
Model	GLY45RAB	GLY45RAB
Power (hp)	1/6	1/6
Cooling power (W)	220	220
Evaporation temp. (°C)	-10 / +45	-10 / +45
Climate class (°C)	5 (40°C - 40%)	5 (40°C - 40%)
<b>Refrigerant</b>		
Type	R134a	R134a
Refrigerant quantity (g)	250	250
<b>Electronic Controller</b>		
Brand	Dixell	Dixell
Model	XR30CH	XR30CH
<b>Electrical</b>		
Power input (W/A)	160 / 1,1	190 / 1,2
Power supply (V/Hz)	220-240/50	220-240/50
220V/60Hz	no	no
<b>Packaging details</b>		
Packed volume (m <sup>3</sup> )	0,55	0,65
Gross weight (kg)	100	160
Net weight (kg)	85	145