



06/2017

Mod: N65/R316G/EL

Production code: 10121702-Q-0-0 (U3)



Diamond
catering equipment

Model	N65/R212G/EL	N65/R316G/EL
		
Production code	10121701-P-0-0	10121702-P-0-0
Description	Refrigerated base, with special feet H95/155	Refrigerated base, with special feet H95/155
Light	no	no
Key lock	no	no
Range (°C)	-2° +8°	-2° +8°
Operating Mode	Ventilated	Ventilated
External Dimensions		
Width (mm)	1200	1600
Depth/with open drawers (mm)	600 / 1195	600 / 1195
Worktop height (mm)	615 / 675	615 / 675
Internal Dimensions		
Width (mm)	780	1215
Depth (mm)	495	495
Height (mm)	410	410
Gross capacity (L)	158	247
Defrost		
Type of defrost	Automatic	Automatic
No. of defrost in 24h	4	4
Evaporation of defrost water	Automatic	Automatic
Compressor		
Brand	Cubigel	Cubigel
Model	GLY45RA_b	GLY45RA_b
Power (hp)	1/6	1/6
Cooling power (W)	220	220
Evaporation temp. (°C)	-10 / +45	-10 / +45
Climate class (°C)	5 (40°C - 40%)	5 (40°C - 40%)
Refrigerant		
Refrigerant fluid / GWP	R134a / 1430	R134a / 1430
Refrigerant charge (kg)	0,240	0,310
Electronic Controller		
Brand	Dixell	Dixell
Model	XR30CH	XR30CH
Electrical		
Power input (W/A)	180 / 1,2	215 / 1,3
Power supply (V/Hz)	220-240/50	220-240/50
220V/60Hz	no	no
Packaging details		
Packed volume (m ³)	0,55	0,65
Gross weight (kg)	100	160
Net weight (kg)	85	145
Efficiency Information		
Energy efficiency class	C	C
Daily Energy Consumption (E24h) (kWh/kg)	2,16	2,84
Annual Energy Consumption (AEC) (kWh/kg)	788	1037
Net volume (L)	110	165
Climate class	5	5