




10/2016




# **Mod: N77/R420G-EL**

**Production code: 10113703-Q-0-0 (U1)**



**Diamond**  
catering equipment

Model	N77/R212G-EL	N77/R316G-EL	N77/R420G-EL
			
Production code	10113701-P-0-0	10113702-P-0-0	10113703-P-0-0
Description	Refrigerated base, with special feet H95/155, 2 drawers	Refrigerated base, with special feet H95/155, 3 drawers	Refrigerated base, with special feet H95/155, 4 drawers
Light	no	no	no
Key lock	no	no	no
Range (°C)	-2° +8°	-2° +8°	-2° +8°
Operating Mode	Ventilated	Ventilated	Ventilated
<b>External Dimensions</b>			
Width (mm)	1200	1600	2000
Depth/with open drawers (mm)	700 / 1295	700 / 1295	700 / 1295
Worktop height (mm)	615 / 675	615 / 675	615 / 675
<b>Internal Dimensions</b>			
Width (mm)	780	1215	1650
Depth (mm)	595	595	595
Height (mm)	410	410	410
Gross capacity (L)	190	296	403
<b>Defrost</b>			
Type of defrost	Automatic by time, stop	Automatic by time, stop	Automatic by time, stop
No. of defrost in 24h	4	4	4
Evaporation of defrost water	Hot gas	Hot gas	Hot gas
<b>Compressor</b>			
Brand	Huayi	Huayi	Huayi
Model	GLY45RAB	GLY45RAB	GLY60RAB
Power (hp)	1/6	1/6	1/5
Cooling power (W)	220	220	296
Evaporation temp. (°C)	-10 / +45	-10 / +45	-10 / +45
Climate class (°C)	5 (40°C - 40%)	5 (40°C - 40%)	5 (40°C - 40%)
<b>Refrigerant</b>			
Type	R134a	R134a	R134a
Refrigerant quantity (g)	250	300	350
<b>Electronic Controller</b>			
Brand	Dixell	Dixell	Dixell
Model	XR30CH	XR30CH	XR30CH
<b>Electrical</b>			
Power input (W/A)	160 / 1,1	180 / 1,2	230 / 1,2
Power supply (V/Hz)	220-240/50	220-240/50	220-240/50
220V/60Hz	no	no	no
<b>Packaging details</b>			
Packed volume (m³)	0,91	1,21	1,50
Gross weight (kg)	119	153	193
Net weight (kg)	94	128	154

Model	N77/R212G-EL4	N77/R316G-EL6	N77/R420G-EL8
			
Production code	10113701-P-0-C	10113702-P-0-E	10113703-P-0-G
Description	Refrigerated base, with special feet H95/155, 4 drawers	Refrigerated base, with special feet H95/155, 6 drawers	Refrigerated base, with special feet H95/155, 8 drawers
Light	no	no	no
Key lock	no	no	no
Range (°C)	-2° +8°	-2° +8°	-2° +8°
Operating Mode	Ventilated	Ventilated	Ventilated
<b>External Dimensions</b>			
Width (mm)	1200	1600	2000
Depth/with open drawers (mm)	700 / 1295	700 / 1295	700 / 1295
Worktop height (mm)	615 / 675	615 / 675	615 / 675
<b>Internal Dimensions</b>			
Width (mm)	780	1215	1650
Depth (mm)	595	595	595
Height (mm)	410	410	410
Gross capacity (L)	190	296	403
<b>Defrost</b>			
Type of defrost	Automatic by time, stop	Automatic by time, stop	Automatic by time, stop
No. of defrost in 24h	4	4	4
Evaporation of defrost water	Hot gas	Hot gas	Hot gas
<b>Compressor</b>			
Brand	Huayi	Huayi	Huayi
Model	GLY45RAB	GLY45RAB	GLY60RAB
Power (hp)	1/6	1/6	1/5
Cooling power (W)	220	220	296
Evaporation temp. (°C)	-10 / +45	-10 / +45	-10 / +45
Climate class (°C)	5 (40°C - 40%)	5 (40°C - 40%)	5 (40°C - 40%)
<b>Refrigerant</b>			
Type	R134a	R134a	R134a
Refrigerant quantity (g)	250	300	350
<b>Electronic Controller</b>			
Brand	Dixell	Dixell	Dixell
Model	XR30CH	XR30CH	XR30CH
<b>Electrical</b>			
Power input (W/A)	160 / 1,1	180 / 1,2	230 / 1,2
Power supply (V/Hz)	220-240/50	220-240/50	220-240/50
220V/60Hz	no	no	no
<b>Packaging details</b>			
Packed volume (m³)	0,91	1,21	1,50
Gross weight (kg)	119	153	193
Net weight (kg)	94	128	154